

Leaders in Flexible Transfer Solutions

**Central Sales and Manufacturing**

Tel: +44 (0) 1933 673699 fax: +44 (0) 1933 675819  
19 The Trinity Centre  
Park Farm Industrial Estate,  
Wellingborough, NN8 6ZB

**Northern Service Centre**

Tel: +44 (0) 1706 756400 Fax: +44 (0) 1706 379567  
Todmorden Road,  
Littleborough,  
OL15 9EG

## Supergiene - SE

**Description:** A good quality brewery hose manufactured for arduous service

**Liner:** White, smooth bore, chlorobutyl rubber

**Construction:** Reinforced with Synthetic fibre plies

**Cover:** Red as standard but also available in a variety of different colours please ask our sales office

**Terminations:** Series 7000 hygienic permanently attached coupling

**Note :** All properties at ambient temperature. Test pressure is 1.5 times working pressure in all cases

Hoses may on request be supplied with higher working and test pressures



**Approvals:** FDA CFR 21 177.2600, BGA XXIA Cat.2

**Features:**

- Liner will not affect taste, colour or odour of product
- Smooth internal bore minimises product hold up
- Abrasion resistant covering for arduous use
- Tough reinforcement for long service life
- Designed to withstand crushing and handling abuse
- Detergent or Caustic (CIP) cleanable
- Steam cleanable (short duration) SIP

### Hose Assemblies

All hose assemblies are manufactured using our series 7000 Coupling which offers enhanced hygiene and safety with improved service life.

FlexRite Chemgiene manufacture all fittings in 316 stainless steel suitable for food and pharmaceutical use.

Each assembly is hard stamped with the date of assembly and test, the test pressure and a unique manufacturing reference - providing product traceability and ease of re-ordering.

Products are accompanied by a certificate of compliance and test to EN10204 Type 2.2.

FlexRite Chemgiene supply the complete range of hygienic fittings including RJT, IDF/ISS, DIN, SMS and Tri-Clamp and general industry standard hose fittings. We also have extensive experience in the manufacture of special fittings to suit specific customer requirements.

Hose Part Number	Bore Diameter		Working Pressure	Min Bend Radius	Weight	Vacuum Rating	Working Temp		Min Burst Pressure
	Nominal						Min °C	Max °C	
	in	mm							
2009	1	25	10	250	0.8	NONE	-40	120	30
2009	1½	40	10	380	1.7	NONE	-40	120	30
2009	2	50	10	510	2.4	NONE	-40	120	30
2009	2½	63	6	630	3.0	NONE	-40	120	30
2009	3	75	6	760	4.3	NONE	-40	120	30

**Options :** 1) Recognition/External Smoothing - Heat shrink PVC in various colours. 2) Sight Glass - In-line Non-Glass Sight Glass incorporated into hose assembly. 3) End Protection - Rubber nut protection rings. 4) Special Couplings - 45° and 90° Elbows, Valves, Quick release couplings.

Website : [www.flexritechemgiene.com](http://www.flexritechemgiene.com)

E-mail: [enquiry@flexritechemgiene.com](mailto:enquiry@flexritechemgiene.com)

Telephone: +44 (0) 1933 673699