

Leaders in Flexible Transfer Solutions

Central Sales and Manufacturing

Tel: +44 (0) 1933 673699 Fax: +44 (0) 1933 675819
19 The Trinity Centre
Park Farm Industrial Estate,
Wellingborough, NN8 6ZB

Northern Service Centre

Tel: +44 (0) 1706 756400 Fax: +44 (0) 1706 379567
Todmorden Road,
Littleborough,
OL15 9EG

Chem-Rite T5050G

Description: An industry standard Acid and Chemical Suction and Delivery Hose. Suitable for 90% of existing chemicals.

Liner: Transparent (XLPE) cross linked polyethylene.

Construction: Reinforced with high tensile textile cords and embedded steel helix.

Cover: Green EPDM Rubber with T-505 Brand in Orange Letters

Terminations: Series 7000 hygienic permanently attached coupling

Note : All properties at ambient temperature. Test pressure is 1.5 times working pressure in all cases

Hoses may on request be supplied with higher working and test pressures



Approvals:

Features:

- Smooth internal bore minimises product hold up
- High flexibility
- 16 Bar working pressure

Hose Assemblies

All hose assemblies are manufactured using our series 7000 Coupling which offers enhanced hygiene and safety with improved service life.

FlexRite Chemgiene manufacture all fittings in 316 stainless steel suitable for food and pharmaceutical use.

Each assembly is hard stamped with the date of assembly and test, the test pressure and a unique manufacturing reference - providing product traceability and ease of re-ordering.

Products are accompanied by a certificate of compliance and test to EN10204 Type 2.2.

FlexRite Chemgiene supply the complete range of hygienic fittings including RJT, IDF/ISS, DIN, SMS and Tri-Clamp and general industry standard hose fittings. We also have extensive experience in the manufacture of special fittings to suit specific customer requirements.

Hose Part Number	Bore Diameter		Working Pressure	Min Bend Radius	Weight	Vacuum Rating	Working Temp		Min Burst Pressure
	Nominal						Min °C	Max °C	
	in	mm	bar (g)	mm	kg/m	bar (g)			bar (g)
4029	¾	20	16	125	0.7	-0.9	-30	65	48
4029	1	25	16	150	0.8	-0.9	-30	65	48
4029	1¼	32	16	175	1.0	-0.9	-30	65	48
4029	1½	40	16	225	1.1	-0.9	-30	65	48
4029	2	50	16	275	1.5	-0.9	-30	65	48
4029	2½	63	16	300	2.2	-0.9	-30	65	48
4029	3	75	16	350	2.8	-0.8	-30	65	48

Options: 1) Recognition/External Smoothing - Heat shrink PVC in various colours. 2) Sight Glass - In-line Non-Glass Sight Glass incorporated into hose assembly. 3) End Protection - Rubber nut protection rings. 4) Special Couplings - 45° and 90° Elbows, Valves, Quick release couplings.

Website : www.flexritechemgiene.com

E-mail: enquiry@flexritechemgiene.com

Telephone: +44 (0) 1933 673699