

Central Sales and Manufacturing

Tel: +44 (0) 1933 673699 Fax: +44 (0) 1933 675819
19 The Trinity Centre
Park Farm Industrial Estate,
Wellingborough, NN8 6ZB

Northern Service Centre

Tel: +44 (0) 1706 756400 Fax: +44 (0) 1706 379567
Todmorden Road,
Littleborough,
OL15 9EG

Super-Flex Metallic 321/CS



Description: A stainless steel annular corrugated hose with a close pitch for extreme flexibility

Liner: 321 SS / DIN 1.4541 stainless steel, corrugated, close pitch

Construction: Independent overbraid welded at fittings

Cover: Single stainless steel braid, 304 SS / DIN 1.4301

Terminations: Welded ferrule and coupling in Carbon steel

Note: Hoses may on request be supplied with higher working and test pressures

Approvals: ISO 10380

Features:

- An extremely flexible hose (in metallic hose terms) exceeding Type 1 ISO 10380 flexibility by 25%
- Suitable for suction (vacuum) duty
- High cycle life for dynamic bending

Hose Assemblies

These hose assemblies are manufactured with a fully welded hose ferrule and coupling, providing a rugged design for maximum service life.

Each assembly is engraved with our unique manufacturing reference—providing traceability and ease of re-ordering.

Products are accompanied by a certificate of compliance and test to EN10204 Type 2.2.

FlexRite Chemgiene supply the complete range of hygienic fittings including RJT, IDF/ISS, DIN, SMS and Tri-Clamp and general industry standard hose fittings. We also have extensive experience in the manufacture of special fittings to suit specific customer requirements.

Hose Part Number	Bore Diameter Nominal		Static Working Pressure bar (g)	Bend Radius		Weight Kg/m	Vacuum Rating bar (g)	Working Temp		Min Burst Pressure bar (g)
	in	mm		Dynamic mm	Static mm			Min °C	Max °C	
9060	¼	6	200	140	20	0.2	-1.0	-200	700	680
9060	⅜	10	131	150	20	0.3	-1.0	-200	700	465
9060	½	13	115	124	25	0.4	-1.0	-200	700	410
9060	¾	20	69	169	38	0.5	-1.0	-200	700	220
9060	1	25	54	195	45	0.7	-1.0	-200	700	170
9060	1¼	32	46	225	58	1.0	-1.0	-200	700	170
9060	1½	40	37	225	70	1.3	-1.0	-200	700	150
9060	2	50	40	293	85	2.0	-1.0	-200	700	156
9060	2½	65	31	345	105	2.8	-1.0	-200	700	105
9060	3	80	30	520	180	4.3	-1.0	-200	700	97
9060	4	100	20	600	210	5.6	-1.0	-200	700	65
9060	6	150	14	-	290	8.0	-1.0	-200	700	48

Options: 1) Heating—Jacketed duplex assemblies. 2) Special Couplings — 45° and 90° Elbows, Valves, Quick release couplings

Website : www.flexritechemgiene.com

E-mail: enquiry@flexritechemgiene.com

Telephone: +44 (0) 1933 673699