

Leaders in Flexible Transfer Solutions

Central Sales and Manufacturing

Tel: +44 (0) 1933 673699 fax: +44 (0) 1933 675819
19 The Trinity Centre
Park Farm Industrial Estate,
Wellingborough, NN8 6ZB

Northern Service Centre

Tel: +44 (0) 1706 756400 Fax: +44 (0) 1706 379567
Todmorden Road,
Littleborough,
OL15 9EG

Silpure 100P



Description:	An ideal choice for filling equipment (particularly aseptic), load cell connectors and food processing.
Liner:	Natural, smooth bore, silicone rubber, platinum cured.
Construction:	Reinforced with one ply of polyester fibre.
Cover:	Natural, silicone rubber, platinum cured, smooth
Terminations:	Series 7000 hygienic permanently attached coupling
Note :	All properties at ambient temperature. Test pressure is 1.5 times working pressure in all cases Hoses may on request be supplied with higher working and test pressures

Approvals: FDA CFR 21 177.2600, USP XXI ClassVI, German BgVV XVA & LIIA

Features:

- Liner will not affect taste, colour or odour of product
- Smooth internal minimises product hold up
- Suitable for dairy products
- High flexibility for frequent flexing applications
- A lightweight hose for ease of handling
- Suitable for suction (vacuum) duty
- Detergent or caustic (CIP) cleanable
- Steam cleanable (short duration) SIP
- Autoclavable

Hose Assemblies

All hose assemblies are manufactured using our series 7000 Coupling which offers enhanced hygiene and safety with improved service life.

FlexRite Chemgiene manufacture all fittings in 316 stainless steel suitable for food and pharmaceutical use.

Each assembly is hard stamped with the date of assembly and test, the test pressure and a unique manufacturing reference - providing product traceability and ease of re-ordering.

Products are accompanied by a certificate of compliance and test to EN10204 Type 2.2.

FlexRite Chemgiene supply the complete range of hygienic fittings including RJT, IDF/ISS, DIN, SMS and Tri-Clamp and general industry standard hose fittings. We also have extensive experience in the manufacture of special fittings to suit specific customer requirements.

Hose Part Number	Bore Diameter		Working Pressure	Min Bend Radius	Weight	Vacuum Rating	Working Temp		Min Burst Pressure
	Nominal						Min °C	Max °C	
	in	mm	bar (g)	mm	kg/m	bar (g)			Bar (g)
3027	3/8	10	9	40	0.2	No Data	-40	150	29
3027	1/2	13	9	50	0.2	No Data	-40	150	17
3027	3/4	20	6	75	0.4	No Data	-40	150	12
3027	1	25	4	100	0.5	No Data	-40	150	9

Options : 1) Recognition/External Smoothing - Heat shrink PVC in various colours. 2) Sight Glass - In-line Non-Glass Sight Glass incorporated into hose assembly. 3) End Protection - Rubber nut protection rings. 4) Special Couplings - 45° and 90° Elbows, Valves, Quick release couplings.

Website : www.flexritechemgiene.com

E-mail: enquiry@flexritechemgiene.com

Telephone: +44 (0) 1933 673699