

Leaders in Flexible Transfer Solutions

Central Sales and Manufacturing

Tel: +44 (0) 1933 673699 fax: +44 (0) 1933 675819
19 The Trinity Centre
Park Farm Industrial Estate,
Wellingborough, NN8 6ZB

Northern Service Centre

Tel: +44 (0) 1706 756400 Fax: +44 (0) 1706 379567
Todmorden Road,
Littleborough,
OL15 9EG

Silpure Platinum SMSP Elbows and U Bends

Description:	Suitable for use in food, beverage and pharmaceutical applications, where the highest levels of purity are critical.
Liner:	Natural, smooth bore, extruded silicone rubber platinum cured.
Construction:	Reinforced with plies of polyester fibre and fully embedded stainless steel wire helix
Cover:	Natural, silicone rubber, platinum cured, smooth
Terminations:	Series 7000 hygienic permanently attached coupling
Note :	All properties at ambient temperature. Test pressure is 1.5 times working pressure in all cases Hoses may on request be supplied with higher working and test pressures



Approvals: FDA CFR 21 177.2600, German BgVV XVA & LIIA, Italy Gazzetta Ufficiale 1973 and add'ns

Features:

- Liner will not affect taste, colour or odour of product
- Smooth internal bore minimises product hold up
- Suitable for dairy products
- Suitable for suction (vacuum) duty
- Detergent or caustic (CIP) cleanable
- Steam cleanable (short duration) SIP
- Autoclavable

Hose Assemblies

All elbow assemblies are manufactured using our series 7000 Coupling which offers enhanced hygiene and safety with improved service life.

FlexRite Chemgiene manufacture all fittings in 316 stainless steel suitable for food and pharmaceutical use.

Each assembly is hard stamped with the date of assembly and test, the test pressure and a unique manufacturing reference - providing product traceability and ease of re-ordering.

Products are accompanied by a certificate of compliance and test to EN10204 Type 2.2.

FlexRite Chemgiene supply the complete range of hygienic fittings including RJT, IDF/ISS, DIN, SMS and Tri-Clamp and general industry standard hose fittings. We also have extensive experience in the manufacture of special fittings to suit specific customer requirements.

Hose Part Number	Bore Diameter		Working Pressure	Weight	Vacuum Rating	Working Temp		Min Burst Pressure
	Nominal					Min °C	Max °C	
	in	mm						
3017	1	25	4.5	0.7	-1.0	-60	170	18
3017	1½	38	4.5	1.0	-1.0	-60	170	18
3017	2	51	4.5	1.6	-1.0	-60	170	18
3017	2½	64	4.5	2.1	-1.0	-60	170	18
3017	3	76	4.5	2.5	-1.0	-60	170	18
3017	4	102	4.5	2.9	-1.0	-60	170	18

Options: 1) Recognition/External Smoothing - Heat shrink PVC in various colours. 2) Sight Glass - In-line Non-Glass Sight Glass incorporated into hose assembly. 3) End Protection - Rubber nut protection rings. 4) Special Couplings - 45° and 90° Elbows, Valves, Quick release couplings.

Website : www.flexritechemgiene.com

E-mail: enquiry@flexritechemgiene.com

Telephone: +44 (0) 1933 673699